

IMPORTANT



Do not dilute the contents of this container all at once. Only dilute enough Activator-V for each use.

PLEASE NOTE: EcoCare Activator-V is 5 times stronger than our original EcoCare Activator.

Please read the label carefully before use of the product. For best results, add at night (or during period of least usage).

Need some help?

Our team of experienced wastewater consultants is ready to help analyse your situation, resolve any issues you may have, and answer your questions.



ODOUR CONTROL



Dilute 1 part Activator-V with 50 parts cold water and spray to destroy odours in rubbish bins, toilets, kennels etc. To remove odours from carpets, apply liberally, leave for 5-10 minutes and then dab dry.

REUSABLE HAND PUMP



3 full pumps are equal to 25ml of Activator-V or one person's weekly dose. Use pump for greater convenience and better measurement accuracy. Please do not throw away pump as it is reusable.

CLEANING



Dilute 1 part Activator-V with 25 parts cold water for household cleaning. Spray on, leave for a few minutes, and then rinse off. Suitable for use on showers, floors, toilets, sinks, tiles, windows, BBQs and all other hard surfaces.

SEPTIC/AWT SYSTEMS*



When priming the system for the first time, flush 800ml of Activator-V down the toilet - this only needs to be done once. When maintaining the system, continue to add 25ml of Activator-V per person to the system weekly, via toilet or drains. When adding via drains follow with 1 litre of cold water.

ABSORPTION TRENCHES*



To remove trench blockages and odours, flush 800ml of Activator-V down the toilet - this only needs to be done once - and follow up by adding 150ml of Activator-V to the system per week via toilet or drains. A minimum of 3 litres of Activator-V will need to be added over a 3-4 month period to unblock trenches.

GREYWATER/GREASE TRAP



To reduce build-up and odour, add 100ml of Activator-V followed by 1 litre of cold water per week. For best results, add small amounts each night. Prior to first application, flush grease trap and line with cold water.

DRAINS



To remove blockages and destroy odours, add 50ml of Activator-V followed by 1 litre of cold water to affected drain daily until blockage is cleared and odour eliminated.

*for repriming/reseeding systems, please refer to your Ecocare Enhancer Kit packaging for instructions.