

## GT PLUS Instructions



EcoCare GT Plus is a blend of select fat and grease digesting bacteria which rapidly break down fat, oil and grease in your waste system without adding any harsh chemicals. Your drain lines and pipes will be clear and odourless, preventing blockages and improving the performance of your grease trap.

### ODOUR AND BLOCKAGE REMOVAL



Perform the following steps daily until the odour or blockage is removed.

- 1 Identify your recommended dosage using the table below. If you have any questions please contact your supplier or contact us directly.
- 2 At the end of the day, add the recommended dosage of EcoCare GT Plus into the main kitchen drain line which has the odour or blockage.  
**Tip:** to increase its effectiveness, add GT Plus at least 1 hour after the last dishwashing cycle has ended.
- 3 Immediately follow up with a cup (250ml) of room temperature water into the same drain.
- 4 Repeat steps 1 and 2 each day until the odour or blockage is removed.

### GREASE TRAP MAINTENANCE



- To prevent odours and blockages you can continue to dose your wastewater system with your remaining EcoCare GT Plus.
- For more economical wastewater or grease trap maintenance to ensure odours and blockages don't return, use EcoCare Activator.
- For easy application and best results, apply GT Plus using one of our Automated Dosing Systems.

Max. Meals Per Day*	Grease Trap Size (L)	EcoCare GT Plus**	If used each day, a 20L drum lasts
0 – 100	100 - 750	100 mL / day	6 months
101 – 400	751 – 2,000	150 mL / day	4 months
401 - 700	2,001 – 3,500	300 mL / day	2 months
	3,501 – 5,000	650 mL / day	1 month
	<b>5,001 – 10,000</b>	<b>1.4 L / day</b>	<b>2 weeks</b>

\*For grease traps that have a mismatch between meals per day and grease trap size, base the dosage on meals per day

\*\*By dosing pump, or add extra 20% for hand dosing.